



## Telekommunikations-Anschluss-Einheiten TAE 2x6/6 Standard



### Aufputz

TAE 2x6/6 NF/F AP pws  
TAE 2x6/6 NF/F AP rws

### Bestell-Nr.

1-672.05.5.09  
1-672.05.5.19

### Farbe Gewicht VPE

pws	42 g	10
rws	42 g	10
pws	42 g	360
rws	42 g	360

TAE 2x6/6 NF/F AP pws  
TAE 2x6/6 NF/F AP rws

1-673.05.5.09  
1-673.05.5.19

pws	42 g	360
rws	42 g	360



### Unterputz

TAE 2x6/6 NF/F UP pws  
TAE 2x6/6 NF/F UP rws

### Bestell-Nr.

1-675.05.5.09  
1-675.05.5.19


### Farbe Gewicht VPE

pws	65 g	10
rws	65 g	10
pws	65 g	240
rws	65 g	240

TAE 2x6/6 NF/F UP pws  
TAE 2x6/6 NF/F UP rws

1-674.05.5.09  
1-674.05.5.19

pws	65 g	240
rws	65 g	240



### Unterputz kombinationsfähig

TAE 2x6/6 NF/F UPK pws  
TAE 2x6/6 NF/F UP0 rws

### Bestell-Nr.

1-676.05.5.09  
1-671.05.5.19

### Farbe Gewicht VPE

pws	53 g	10
rws	50 g	10

UP0 = UPK ohne Zentralstück  
(ohne Abbildung)

pws = perlweiß (RAL 1013)  
rws = reinweiß (RAL 9010)

